

SOFFITE

An ingenious, discreet,
angle luminaire, designed
to form a line of light
and be adapted to all your projects.



BVCert. 6037554



The various modules can be put together in such a way as to create a lighting strip between wall and ceiling, or vertically in a corner.

The Soffite is fitted with very low consumption sources.

Elegant

With a slender 92 mm footprint and only 80 mm angle protrusion at 45°, the Soffite is particularly discreet!

Economic

Save power thanks to the LED sources, the presence detection, or the dimmable ballasts!

Practical

Easy to fit, it allows the supply cables to pass at the rear and protects access to the lamps via an ingenious locking system.

**DISCREET AND ORIGINAL,
THE SOFFITE IS A
PARTICULARLY INGENUOUS
ANGLE LUMINAIRE THAT CAN
BE ADAPTED
TO YOUR PROJECTS.**



Have your Soffite made to measure

Determine the desired length.

Minimum 615 mm, maximum 1620 mm with detector.

Outside these dimensions, please enquire.


Send us your specifications.

However, certain options (detectors, batteries, etc.) may create non-illuminating zones, which will be indicated to you.

Together, we validate your project.

Prior to final confirmation, we send you a drawing, a quote, and a delivery lead time.

You will receive a bespoke Soffite luminaire specific to your architectural project.









FEATURES:

- Decorative luminaire for corner-mounting
- Body and end caps in white lacquered aluminium
- Opalescent polycarbonate diffuser
- CCT 4000 K, CRI min. 80
- Twin rear cable entries

OPTIONS AVAILABLE ON REQUEST:

- 3000 K LEDs
- Standby LED




Length (mm)	Length with detection (mm)	Power (W)	Luminaire light output (lm)	Luminaire efficacy (lm/W)	Code
615	760	12	1330	111	3015 04--
		18	2270	126	3016 04--
915	1060	14	1680	120	3017 04--
		26	3250	125	3018 04--
1195	1340	18	2350	131	3019 04--
		33	4240	128	3020 04--
1475	1620	26	3340	128	3021 04--
		41	5340	130	3022 04--


Lumen maintenance: L80B10 / over 72,000 h
L90B50 / 52,000 h

Coding colour temperature 3000 K : example 4000K : 3015 04--
replace 4 with 3 3000K : 3015 03--

Coding: replace the two dashes (--) by the corresponding figures:
example 3015 04--

- 00 NO DETECTION
- 21 DALI DIMMABLE + SWITCH DIMMING
- 12 WITH DETECTION PRO
- 14 WITH PRO DETECTION + EXTINCTION WARNING
- 15 WITH PRO DETECTION + STANDBY WARNING
- 16 WITH PRO DETECTION + RADIO-CONTROL
- 04 SLAVE VERSION + EXTINCTION WARNING
- 05 SLAVE VERSION + STANDBY WARNING

 Tamper-proof tool (pliers) to be ordered separately
code : 9800 0009

 Radio remote control to be ordered separately
code : 9800 0010

Additional options SOFFITE

Coding:
add the corresponding suffix to the product code

example : 3015 0400 ----

- 9801 IN-LINE FITTING (LEFT- AND RIGHT-HAND ENDS OPEN)
- 9803 IN-LINE FITTING (RIGHT-HAND END OPEN)
- 9804 IN-LINE FITTING (LEFT-HAND END OPEN)

DETAILS



