



Tubular luminaire type FILE LED from SÉCURLITE or technically equivalent:

- Dimensions: 690 or 970 or 1250 or 1530 mm – two diameters: Ø 70 and 100 mm
- Class I – IP67 – IK11+ / 80J – VK41 – 850°C – CRI 80 – SDCM 3 – photobiological hazard: RG0
- Opal polycarbonate body with white reflector plate, thickness 4 mm (70 Ø) or 3 mm (100 Ø)
- Decorative internal polyamide trims
- Polished 304L stainless steel end caps or stainless steel (depending on the version)
- Closure by 2 stainless steel CHC screws at each end
- Plug-in terminal block
- Nickel-plated brass IP67 cable gland at one end
- Protective vent for a long lasting seal (ø 100 mm only)
- *CCT, power, luminaire output and efficacy: refer to the technical data sheet according to product code*
- Options available on request: with detection Pro, DALI dimmable + switch dimming + standby warning, with Pro detection + extinction warning, with Pro detection + standby warning, with Pro detection + radio control + radio control, slave version + extinction warning, slave version + standby warning. *Refer to the technical data sheet according to product code*
- Range available in 3000 and 4000 K
- Lumen maintenance: L80B10 / over 72,000 hr – lumen maintenance: L90B50 / 52,000 hr - 5-year warranty
- Eligible for the BAR-EQ-110 for detection versions, for the BAT-EQ-127 for Dali version with light output ≥ 3000 lm, for the IND-BA-116 (except 7540xxxx references), RES-EC-104 energy economy certificates
- Labelled range Origine France Garantie
- Repairable luminaire. Spare parts available on demand.

*Technical and dimensional data are given for information only and may be modified at any time without notice.
Please enquire before ordering.*