

Specification text

FILA 2 LED - FP0023



Tubular luminaire type FILA 2 LED from SÉCURLITE or technically equivalent:

- Dimensions: 690 or 970 or 1250 or 1530 mm two diameters: Ø 70 and 100 mm
- Class I IP67 IK10 / 20J VK21 850°C CRI 80 SDCM 3 photobiological hazard: RG0
- Opal polycarbonate diffuser for FILA2 70, FILA2 100 and FILA2 70 PC/PMMA or clear diffuser for FILA2 with optics (40°, 60°, 90°, batwing, wallwasher) and for FILA2 70 with louvres 2 mm thick
- Polycarbonate body, 2mm thick
- Decorative internal polyamide trims
- Polished 304L end caps or 316L stainless steel (depending on the version)
- · Closure by 2 stainless steel CHC screws at each end
- Plug-in terminal block
- ISO M20 nickel-plated brass IP67 cable gland at one end
- Protective vent for a long-lasting seal (Ø 98 mm only)
- Kit of two 304L and 316L stainless fittings for wall mounting, standard screw fixing and suspended mounting (must be ordered separately)
- Kit of two 304L stainless fittings for turnbuckle fixing (must be ordered separately)
- CCT, power, luminaire output and efficacy: refer to the technical data sheet according to product code
- Options available on request: with detection Pro, DALI dimmable + switch dimming + standby warning, with Pro detection + extinction warning, with Pro detection + standby warning, with Pro detection + radio control + radio control, slave version + extinction warning, slave version + standby warning. Refer to the technical data sheet according to product code
- Range available in 3000 and 4000 K
- Fila 2 70: lumen maintenance: L80B10 / over 72,000 hr lumen maintenance: L90B50 / 52,000 hr 5-year warranty
- Fila 2 100: umen maintenance: L80B10 / over 72,000 hr 5-year warranty
- Eligible for the BAR-EQ-110 for detection versions, BAT-EQ-127 for Dali version with light output ≥ 3000 lm, IND-BA-116, RES-EC-104 (ceiling mounting only) energy economy certificates
- Labelled range Origine France Garantie
- Repairable luminaire. Spare parts available on demand.

Technical and dimensional data are given for information only and may be modified at any time without notice. Please enquire before ordering.