

BORGO PRISON

Wall-mounting fitting
with switch
for correctional environments.



BVCert. 6037554





Borgo Prison



Mini-Borgo Prison




FEATURES:

- Very compact cell wall fitting
- Rip-out resistant
- > 65° inclined top
- Vandal-resistant switch
- Body in ZP 10/10 steel
- Frame in ZP 20/10 steel
- Polyester powder-coated finish
- Opalescent polycarbonate diffuser
- CCT 4000 K, CRI min. 80
- Stainless steel vandal-resistant screws
- RAL 9003


OPTIONS AVAILABLE ON REQUEST:

- 3000 K LEDs
- Switch on the left side


Borgo
code : 5324 1400




Borgo Prison



Mini-Borgo Prison
code : 5340 0400



Mini-Borgo Prison



BORGO IP 65 with switch

220-240 V AC / 50 / 60 Hz



RoHS

direct 532

| Length (mm) | Power (W) | Luminaire light output (lm) | Luminaire efficacy (lm / W) | Code switch on right |
|-------------|-----------|-----------------------------|-----------------------------|-------------------------|
| 390 | 8 | 725 | 91 | 5324 1400 |
| | 17 | 1700 | 100 | 5325 1400 |

Lumen maintenance: L80B10 / over 72,000 h
L90B50 / 52,000 h

Coding colour temperature 3000 K :
replace 4 with 3

example 4000K : 5324 1400
3000K : 5324 1300

Vandal-resistant tool (bit) to be ordered separately
code : 9800 0004

BORGO IP 20 with switch and socket

220-240 V AC / 50 / 60 Hz



RoHS

direct 532

| Length (mm) | Power (W) | Luminaire light output (lm) | Luminaire efficacy (lm / W) | Code switch on the right side |
|-------------|-----------|-----------------------------|-----------------------------|----------------------------------|
| 390 | 8 | 725 | 91 | 5326 1400 |
| | 17 | 1700 | 100 | 5327 1400 |

Lumen maintenance: L80B10 / over 72,000 h
L90B50 / 52,000 h

Coding colour temperature 3000 K :
replace 4 with 3

example 4000K : 5326 1400
3000K : 5326 1300

Vandal-resistant tool (bit) to be ordered separately
code : 9800 0004

Additional options BORGO

Coding:
add the corresponding suffix to the product code

example : 5324 1400 ----

9413 FLAT DUROFLAM® DIFFUSER
9415 FLAT OPALESCENT PC DIFFUSER


DETAILS

| Power (W) | Luminaire light output (lm) | Luminaire efficacy (lm/W) | Code switch on the right side |
|-----------|-----------------------------|---------------------------|----------------------------------|
| 11 | 925 | 84 | 5340 0400 |

Lumen maintenance: L80B10 / over 72,000 h
L90B50 / 52,000 h

Coding colour temperature 3000 K :
replace 4 with 3

example 4000K : 5340 0400
3000K : 5340 0300

 Vandal-resistant tool (bit) to be ordered separately
code : 9800 0004

 **DETAILS**

