








Products classified by VK[®] rating

VK [®] rating							
20				Talk			
21	Fila ²	Fila ²			Senspot	Fila ²	
22	Duropark Jono Fila ² (VAV)	Duropark Fila ² (VRS)	Soffite			Fila ² (VRS)	Decade Rocca
24				Smile			
25	Effice (general lighting)	Effice (general lighting) Effice Corridor Effice Stairway					
26	Voila Voila Access Voila Start Voila Asymmetric	Voila Voila Access Voila Start					
32					Vandal-resistant Senspot		
35	Bang Round Bang Square Bang Rectangle						
36	P600 LED	Bang Round Bang Square Bang Rectangle		P600 E LED			
41	Fila	Fila				Fila	
42	Fila (VRS)	Fila (VRS)				Fila (VRS)	
44	Casemate						
45	Punto Izu / Izumi Titan Compact Aleane Aleane asymmetric Vauban A ASL Santa / Buda	Punto Aleane		Punto* Izu / Izumi* Santa / Buda*	Punto*		
46	Borgo Borgo Prison Mini-Borgo Prison	Titan Compact Vauban ASL		Titan Compact E Vauban E ESL Brikette stainless			
55	Rondo / Rondino Rueda Aki / Akita Titan C95 Titan S3 Urbaline						
56		Rondo/Rondino Urbaline Titan C95 Titan S3	Urbaline Titan A45 / A30 Titan S2 Titan video surveillance	Rondo / Rondino* Rueda* Aki / Akita* Titan E Titan S4	Rondo / Rondino*		

(VRS): vandal-resistant screws

* flush-mounting version (option 9802)

VK[®] ratings













VK[®] vandal resistance rating

VK [®] ratings	1 st position	2 nd position	(3 rd position)
0	< 10 joules	no protection	no protection
1	10 joules *	standard fastenings	flame resistant
2	20 joules *	vandal-resistant fastenings (or secure closure)	graffiti resistant
3	50 joules *	rip-out-resistant	increased UV resistance (tropicalization)
4	80 joules	rip-out-resistant + standard fastenings	resists marine environment
5	120 joules	rip-out-resistant + vandal-resistant fastenings	-
6	160 joules	anti-ligature + vandal-resistant fastenings	-
7	200 joules	-	-
8	-	-	-
9	-	-	-

*By virtue of their characteristics, anti-ligature luminaires are also rip-out-resistant.
The figure in the 3rd position is optional.*

* Standardized values as per EN 62262: see IK rating

PICTOGRAMS

 850° Incandescent wire test	 Bulkhead fitting	 Suspended fitting
 2-point tamper-resistant screws	 Ceiling fitting	 Bollards
 Tamper-proof Torx screws	 Corner-mounting fitting	
 Standard crosspoint screws	 Flush wall-mounting	
 Standard Allen screws	 Flush-mounting ceiling fitting	