


## Specification text

VOILA LED ASYMMETRIC - FP0002-C



Wall mounted luminaire type VOILA LED ASYMMETRIC from SÉCURLITE or technically equivalent:

- Dimensions: Ø 340 x 105 mm
- Class II – IP55 – IK10 / 20J – VK26 – 850°C – CRI 80 – SDCM 3 – photobiological hazard: RG0
- Polycarbonate base available in white, black, grey
- Opalescent polycarbonate diffuser with 3 captive vandal-resistant stainless steel screws
- Anti-rip-out-skirt, 4 internal fixing points
- Side and rear cable entries for plastic conduit for renovation – supply terminal block: automatic dual-entry for 1.5 mm<sup>2</sup> conductors
- *CCT, power, luminaire output and efficacy: refer to the technical data sheet according to product code*
- Options available on request: with detection, with Pro detection + extinction or standby warning, with Pro detection + radio control, with Pro detection + extinction or standby + radio control, slave version + extinction or standby warning, slave version + extinction or standby warning + radio control. *Refer to the technical data sheet according to product code*
- Range available in 3000 and 4000 K
- Lumen maintenance: L80B10 / over 72,000 hr - Lumen maintenance: L90B50 / 52,000 hr – 5-year warranty
- Eligible for the BAR-EQ-110 for the detection versions
- Labelled range Origine France Garantie
- Repairable luminaire

*Technical and dimensional data are given for information only and may be modified at any time without notice.  
Please enquire before ordering*