

## Specification text

BANG ROUND LED - FP0009



### BANG ROUND LED

Wall or ceiling mounted luminaire type BANG ROUND LED from SÉCURLITE or technically equivalent:

- Dimensions: Ø 320 x 103 mm
- Class II – IP55 – IK11 / 50J – VK35 version wall – VK36 version ceiling – 850°C – CRI 80 – SDCM 3 – photobiological hazard: RG0
- Consolidated polycarbonate base available in white
- Opalescent polycarbonate diffuser with 3 captive vandal-resistant stainless steel screws
- Screw washers: through-coloured polycarbonate
- Anti-rip-out-skirt, 4 internal fixing points
- Side cable entries for plastic conduit for renovation – supply terminal block: automatic dual-entry for 1.5 mm<sup>2</sup> conductors
- *CCT, power, luminaire output and efficacy: refer to the technical data sheet according to product code*
- Options available on request: with detection, DALI dimmable, with Pro detection + extinction or standby warning, with Pro detection + radio control, with Pro detection + extinction or standby warning + radio control, slave version + extinction or standby warning, slave version + extinction or standby warning + radio control. *Refer to the technical data sheet according to product code*
- Range available in 3000 and 4000 K
- Lumen maintenance: L80B10 / 72,000 hr – 5-year warranty
- Labelled range Origine France Garantie
- Repairable luminaire

*Technical and dimensional data are given for information only and may be modified at any time without notice.  
Please enquire before ordering.*