

Specification text

BANG RECTANGLE ACCESS LED - FP0011



BANG RECTANGLE ACCESS LED

Wall or ceiling mounted luminaire type BANG RECTANGLE LED ACCESS from SÉCURLITE or technically equivalent:

- Dimensions: 308 x 154 x 103 mm
- Class II – IP55 – IK11 / 50J – VK35 version wall – VK36 version ceiling – 850°C – CRI 80 – SDCM 5 – photobiological hazard: RG0
- Consolidated polycarbonate base available in white
- Opalescent polycarbonate diffuser with 2 captive vandal-resistant stainless steel screws
- Screw washers: through-coloured polycarbonate
- Anti-rip-out-skirt, 4 internal fixing points
- 3 knockout cable entry Ø 10 mm conductors – supply terminal block: automatic dual-entry for conductors
- *CCT, power, luminaire output and efficacy: refer to the technical data sheet according to product code*
- Options available on request: with detection. *Refer to the technical data sheet according to product code*
- Range available in 4000 K
- Lumen maintenance: L70B50 / 50,000 hr – 3-year warranty
- Eligible for the BAR-EQ-110 for the detection versions
- Labelled range Origine France Garantie
- Repairable luminaire

*Technical and dimensional data are given for information only and may be modified at any time without notice.
Please enquire before ordering.*