

Specification text

BANG SQUARE LED - FP0012



BANG SQUARE LED

Wall or ceiling mounted luminaire type BANG SQUARE LED from SÉCURLITE or technically equivalent:

- Dimensions: 308 x 308 x 103 mm
- Class II – IP55 – IK11 / 50J – VK35 version wall – VK36 version ceiling – 850°C – CRI 80 – SDCM 3 – photobiological hazard: RG0
- Consolidated polycarbonate base available in white
- Opalescent polycarbonate diffuser with 4 captive vandal-resistant stainless steel screws
- Screw washers: through-coloured polycarbonate
- Anti-rip-out-skirt, 4 internal fixing points
- 1 knockout cable entry Ø 20,5 mm conductors + 1 cable entry Ø 20,5 mm conductors – supply terminal block: automatic dual-entry for conductors
- *CCT, power, luminaire output and efficacy: refer to the technical data sheet according to product code*
- Options available on request: with detection, DALI dimmable, with Pro detection + extinction or standby warning, with Pro detection + radio control, with Pro detection + extinction or standby warning + radio control, slave version + extinction or standby warning, slave version + extinction or standby warning + radio control.
Refer to the technical data sheet according to product code
- Range available in 3000 K or 4000 K
- Lumen maintenance: L80B10 / 72,000 hr – 5-year warranty
- Labelled range Origine France Garantie
- Repairable luminaire