

## Specification text

SOFFITE LED - FP0017-C



Wall or ceiling mounted luminaire type SOFFITE LED from SÉCURLITE or technically equivalent:

- Dimensions: 615 or 915 or 1195 or 1475 x 92 mm
- Class I – IP42 - IK10 / 20J – VK22 – 850°C – CRI 80 – SDCM 3 – photobiological hazard: RG0
- Base: body and end caps in white lacquered only
- Opalescent polycarbonate diffuser
- Opening secured by special tool
- 2 cable entry conductors at the back
- *CCT, power, luminaire output and efficacy: refer to the technical data sheet according to product code*
- Options available on request: with detection Pro, DALI dimmable + switch dimming + standby warning, with Pro detection + extinction warning, with detection Pro + standby warning, with detection Pro + radio control, slave version + extinction warning, slave version + standby warning. *Refer to the technical data sheet according to product code*
- Range available in 3000 K or 4000 K
- Lumen maintenance: L80B10 / over 72,000 hr - Lumen maintenance: L90B50 / 52,000 hr – 5-year warranty
- Eligible for the BAR-EQ-110 energy economy certificate for detection versions, for the BAT-EQ-127 energy economy certificates for Dali version with light output  $\geq 3000$  lm
- Labelled range Origine France Garantie
- Repairable luminaire