

Specification text

ALEANE LED - FP0037



ALEANE LED

Wall or ceiling luminaire type ALEANE LED from SÉCURLITE or technically equivalent:

- Dimensions: 715 or 1325 x 270 x 62 mm
- Class I – IP55 - IK11+ / 80J – VK45 – 850°C – CRI 80 – SDCM 3 – photobiological hazard: RG0
- Base in 1 mm thick anticorrosion-treated steel with polyester powder-coated finish
- Cover in 1,5 mm thick anticorrosion-treated steel with polyester powder-coated finish
- 3 mm opal polycarbonate diffuser
- Symmetrical or asymmetrical reflector
- Anti-vibration pads under the tubes – protected cable entries – fixing outside the sealed body
- Stainless steel vandal-resistant screws
- Supply terminal block: automatic dual-entry – 3 cable entry for cable gland
- *CCT, power, luminaire output and efficacy: refer to the technical data sheet according to product code*
- Options available on request: with detection Pro, DALI dimmable + switch dimming + standby warning.
Refer to the technical data sheet according to product code
- Range available in 3000 and 4000 K
- Lumen maintenance: L80B10 / over 72,000 hr – lumen maintenance: L90B50 / 52,000 hr - 5-year warranty
- Eligible for the BAR-EQ-110 for detection versions, for the BAT-EQ-127 for Dali version with light output ≥ 3000 lm
- Labelled range Origine France Garantie
- Repairable luminaire