

Specification text

ALEANE ASYMMETRICAL LED - FP0038



ALEANE ASYMMETRICAL LED for pits

Wall or ceiling luminaire type ALEANE ASYMMETRICAL LED from SECURLITE or technically equivalent:

- Dimensions: 1325 x 290 x 65 mm
- Class I – IP65 - IK11+ / 80J – VK45 – 850°C – CRI 80 – SDCM 3 – photobiological hazard: RG0
- Rip-out-resistant body in 1 mm anticorrosion-treated steel with polyester powder-coated finish – white colour with anti-graffiti protection – oil-resistant
- 3 mm Duroflam® diffuser - sealing vent
- Protected cable entries - fixing outside the sealed body
- Stainless steel vandal-resistant screws
- Supply terminal block: automatic dual-entry – side cable-entry glands
- *CCT, power, luminaire output and efficacy: refer to the technical data sheet according to product code*
- Options available on request: DALI dimmable + switch dimming + standby warning. *Refer to the technical data sheet according to product code*
- Range available in 3000 and 4000 K
- Lumen maintenance: L80B10 / over 72,000 hr – lumen maintenance: L90B50 / 52,000 hr - 5-year warranty
- Labelled range Origine France Garantie
- Repairable luminaire

*Technical and dimensional data are given for information only and may be modified at any time without notice.
Please enquire before ordering..*