

# SYSTEO SLIM

Extra-flat,  
vandal-resistant  
architectural luminaire.



BVCert. 6037554





## FEATURES:


- IP65 rated waterproof luminaire with high impact-resistance IK11\*/80 J rated stright aluminium profile.
- Opalescent or clear diffuser with louvres or with optics
- Can be suspension mounted using a mounting kit made from shiny, nickel-plated brass, with 3m stainless steel finger line supplied as standard
- Not apparent quick power connection
- Fine texture RAL 7016 anthracite grey ● finish

## OPTIONS AVAILABLE ON REQUEST:


- Motion detector adjustable via radio-control
- High UV resistance or anti-graffiti coating
- Through wiring
- Side cable entry

*Optional mounting support available to order separately:  
- Suspension kit: 9854 0002*


Systeo SLIM Opalescent




Systeo SLIM Clear + optics 40°




Systeo SLIM Clear + optics 60°





Systeo SLIM Clear + optics 90°



Systeo SLIM Clear + batwing optics



Systeo SLIM Clear + wallwasher optics



Length L (mm)	Power (W)	Luminaire light output (lm)	Luminaire efficacy (lm / W)	Opalescent
1017	9	850	97	5708 14--
1017	14	1400	100	5702 14--
1017	26	2700	104	5703 14--
1297	19	1950	103	5704 14--
1297	37	3800	103	5705 14--

**Lumen maintenance:** L80B10 / over 72,000 h  
L90B50 / 50,000 h

**Coding colour temperature 3000 K :** example 4000K : 5702 14--  
replace 4 with 3 3000K : 5702 13--

**Coding:** replace the two dashes (--) by the corresponding figures:  
example 5702 14--

Vandal-proof tool available to order separately.  
Inset code M4: 9800 0036 + Inset code M5: 9800 0012

Radio remote control to be ordered separately  
code : 9800 0010

- 00 NO DETECTION
- 04 SLAVE VERSION + EXTINCTION WARNING
- 05 SLAVE VERSION + STANDBY WARNING
- 16 WITH PRO DETECTION + RADIO-CONTROL
- 21 DALI DIMMABLE + SWITCH DIMMING
- 44 WITH PRO DETECTION + RADIO-CONTROL + EXTINCTION WARNING
- 45 WITH PRO DETECTION + RADIO-CONTROL + STANDBY WARNING

For ceiling mounting or suspension versions only

Length L (mm)	Power (W)	Luminaire light output (lm) 4000 K*	Luminaire efficacy (lm / W)	Clear
1017	11	1400	127	5736 14--
1017	16	2000	125	5737 14--
1297	16	2100	131	5738 14--
1297	26	3300	127	5739 14--

**Lumen maintenance:** L80B10 / over 72,000 h  
L90B50 / 50,000 h

**Coding colour temperature 3000 K :** example 4000K : 5736 14--  
replace 4 with 3 3000K : 5736 13--

\* For precise figures, please refer to the technical data sheet  
UGR rating to be confirmed by a lighting study.

Vandal-proof tool available to order separately.  
Inset code M4: 9800 0036 + Inset code M5: 9800 0012

Radio remote control to be ordered separately  
code : 9800 0010


**Coding:** replace the two dashes (--) by the corresponding figures:  
example 5736 14--

- 00 NO DETECTION
- 04 SLAVE VERSION + EXTINCTION WARNING
- 05 SLAVE VERSION + STANDBY WARNING
- 16 WITH PRO DETECTION + RADIO-CONTROL
- 21 DALI DIMMABLE + SWITCH DIMMING
- 44 WITH PRO DETECTION + RADIO-CONTROL + EXTINCTION WARNING
- 45 WITH PRO DETECTION + RADIO-CONTROL + STANDBY WARNING

# SYSTEO SLIM – Clear, with optics

For ceiling mounting or suspension versions only

220-240 V AC / 50 / 60 Hz




Length L (mm)	Power (W)	Luminaire light output (lm) 4000 K*	Clear 40° optics	Clear 60° optics	Clear 90° optics	Clear batwing optics	Clear wallwasher optics
1017	9	1050	5714 14--	5719 14--	5724 14--	5729 14--	5734 14--
1017	14	1750	5711 14--	5716 14--	5721 14--	5726 14--	5731 14--
1297	19	2450	5712 14--	5717 14--	5722 14--	5727 14--	5732 14--

**Lumen maintenance:** L80B10 / over 72,000 h  
L90B50 / 50,000 h

\* For precise figures, please refer to the technical data sheet  
UGR rating to be confirmed by a lighting study.

**Coding colour temperature 3000 K :**  
replace 4 with 3

example 4000K : 5731 14--  
3000K : 5731 13--

 Vandal-proof tool available to order separately.  
Inset code M4: 9800 0036 + Inset code M5: 9800 0012

 Radio remote control to be ordered separately  
code : 9800 0010

**Coding:** replace the two dashes (--) by  
the corresponding figures:  
example 5731 14--

- 00 NO DETECTION
- 04 SLAVE VERSION + EXTINCTION WARNING
- 05 SLAVE VERSION + STANDBY WARNING
- 16 WITH PRO DETECTION + RADIO-CONTROL
- 21 DALI DIMMABLE + SWITCH DIMMING
- 44 WITH PRO DETECTION + RADIO-CONTROL + EXTINCTION WARNING
- 45 WITH PRO DETECTION + RADIO-CONTROL + STANDBY WARNING

